

## Cedral fibre cement slates Material Data Sheet

TECHNICAL  
NOTE  
Cr-01/04/en/v4

Cedral fibre cement slates are manufactured from a carefully formulated mix of Portland cement and water, reinforced with a combination of both natural and synthetic fibres. The composition of this formulation means Cedral fibre cement slates have a life expectancy of at least 50 years.

### Authority

- Manufactured to BS EN 492 Fibre cement slates and fittings. Product specification and test methods
- Manufactured under quality managements systems, which meet the requirements of ISO 9001 and systems which comply with the internationally recognised ISO 14001
- Meet the performance requirements of BS 5534 code of practice for slating and tiling

### Advantages of Cedral fibre cement slates

- Low pitch options down to 20°
- Strongest fibre cement slate available
- Best fixed roofing material with 40 fixings per m2
- Perfect for volatile weather conditions
- Maximum design scope with various colours and fixing option for both roof and facade
- Low maintenance
- Sustainable products with low carbon footprint of 16 CO<sub>2</sub>e/m<sup>2</sup>
- A+ Green Guide Rating
- Meet the fire performance classification A2-s1, d0 to EN 13501-1:2018

#### Disclaimer

This information is correct at time of issue. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please contact us to ensure you have the most current version.

All information contained in this document is copyrighted ©.

All figures contained in this document are illustrations and should not be used as construction drawings.

This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use.