

## CEDRAL MOLINA NATURAL SLATE

## Product Data Sheet

Molina Natural Slates are sourced from Northern Spain.

Their coarse texture and blue grey colour will give any roof a natural, traditional look.

Molina come with a 50 year guarantee.



## TECHNICAL DATA

Size of Slate	600 x 300mm	500 x 250mm
Minimum Pitch	25° (110mm Headlap)	25° (110mm Headlap)
Max Pitch	90°	90°
Typical Headlaps	100,110mm	100,110mm
Batten Gauge	245 - 250	200 - 195
Slate Thickness	5-6mm	5-6mm
Covering Capacity	13.1 slates/m <sup>2</sup> (100 headlap) 13.4 slates /m <sup>2</sup> (110mm headlap)	19.6 slates/m <sup>2</sup> (100 headlap) 19.9 slates /m <sup>2</sup> (110mm headlap)
Average Weight per Slate (approx)	2.68kgs	1.75kgs
Typical Quantity per Crate	460 No	600 No
Battens Required (net)	4.00 (net lin.m/m <sup>2</sup> ) at 100 mm headlap	5.00 (net lin.m/m <sup>2</sup> ) at 100 mm headlap
Batten Size Recommended (fixed as per SR82 : 2017)	50 x 25mm for rafter supports not exceeding 400 mm centres 50 x 35mm for rafter supports not exceeding 600 mm centres	
Fixings	Slate nails (40 x 3.35mm) Slate Hooks 2.5mm - 3.00 mm diameter	
Accreditation	EN 12326-1	EN 12326-1
Thermal Cycle Resistance	Class T1	Class T1
Water Absorption	Class W1	Class W1
Sulphur Dioxide Exposure Resistance	Class S1	Class S1

Cedral, as part of Etex Ireland Ltd., is independently certified as meeting requirements of ISO 9001(Quality), ISO 14001 (Environment), ISO 45001 (Safety) and are rated “Excellent” in the BES 6001 Standard for Responsible Sourcing.

Publication Date : January 2021

For further information visit [www.cedral.ie](http://www.cedral.ie), call +353 (0)59 863 1316 or email our technical support department on [info.ireland@cedral.world](mailto:info.ireland@cedral.world)

CI/SfB | | (4-) | Nf9