## CEDRAL




## **TORRES MOLINA SLATES**

## Product data sheet

Torres Natural Slates have a beautiful textured finish and mid-grey colour and are one of the most sought after in the Cedral range.

Originating from Northern Spain, Torres come with a 50 year guarantee.

CI/SfB | (4-) | Nf9 |



Technical data		
Size of slate	600 x 300mm	500 x 250mm
Minimum pitch	25° (110mm headlap)	25° (110mm headlap)
Maximum pitch	90°	90°
Typical headlaps	100, 110mm	100, 110mm
Batten gauge	245-250mm	200-195mm
Slate thickness	5-6mm	5-6mm
Covering capacity	13.1 slates/m² (100mm headlap) 13.4 slates/m² (110mm headlap)	19.6 slates/m² (100mm headlap) 19.9 slates/m² (110mm headlap)
Average weight per slate	2.68kg (approx.)	I.75kg (approx.)
Typical quantity per crate	550 No.	720 No.
Battens required	4.00 (net lin.m/m² at 100 mm headlap)	5.00 (net lin.m/m² at 100 mm headlap)
Batten sizze recommended (fixed as per SR82: 2017)	$50\times25\text{mm}$ for rafter supports not exceeding 400mm centres $50\times35\text{mm}$ for rafter supports not exceeding 600mm centres	$50\times25\text{mm}$ for rafter supports not exceeding 400mm centres $50\times35\text{mm}$ for rafter supports not exceeding 600mm centres
Fixings	Slate nails (40 x 3.35mm) Slate hooks (2.5-3mm diameter)	Slate nails ( $40 \times 3.35$ mm) Slate hooks (2.5-3mm diameter)
Accreditation	EN 12326-1	EN 12326-1
Thermal cycle resistance	ClassTI	ClassTI
Water absorption	Class W I	Class W I
Sulphur dioxide exposure resistance	Class S I	Class S I

Cedral ais independently certified as meeting requirements of ISO 9001 (Quality), ISO 14001 (Environment), OHSAS 18001 (Safety) and are rated "Excellent" in the BES 6001 Standard for responsible sourcing.

For further information visit cedral.ie, call +353 (0)59 863 1316 or email our technical support department on info.ireland@cedral.world





